# **F500 Recirculating Cooler**

# for simple cooling tasks

JULABO F models require very little space and have very low procurement costs. Recirculating coolers of the F Series are a great way to replace costly tap water and are ideal for basic cooling tasks.

### Your advantages

- Environmentally-friendly operation with low energy consumption
- Compact design
- Splash-proof membrane keypad with LED temperature display
- · Straightforward filling and draining
- Filling level indicator
- May be used with water, water/glycol, JULABO Thermal G



### **Technical Data**

Order No.	9620050
Model series	F Series
Category	Recirculating Coolers
Working temperature range (°C)	0 +40
Temperature stability (°C)	0.5
Temperature Control	PID temperature control
Setting / display resolution	0.1 °C
Temperature Display	LED
Cooling capacity (Medium Ethanol)	°C 20 10 5 0 kW 0.5 0.4 0.3 0.25
Pump capacity flow rate (I/min)	24
Pump capacity flow pressure (bar)	0.5
Pump connections	M16x1
Barbed fittings diameter (inner dia. / mm)	8 / 12
Filling volume liters	5 7.5
Refrigerant	R134a
Ambient temperature	540 °C
Dimensions W x L x H (cm)	37.5 x 44 x 59
Weight (kg)	34
Included with each unit	2 each barbed fittings for tubing 8 and 12 mm inner dia. (pump connections M16x1 male)
Cooling of compressor	Air
Available voltage versions	230 V / 50 Hz 230 V / 60 Hz 115 V / 60 Hz 100 V / 50-60 Hz



### **Characteristics**

### Display

# Easy to read

Large LED temperature display for actual value and setpoint (resolution 0.1 °C)

# Operation



Simple and fast Convenient 3-key setpoint adjustment (F models)

### **Temperature Control**

# PID1 Precise

PID Temperature control with set control parameters, temperature stability ±0.02...±0.2 °C

### **JULABO** Contact

JULABO GmbH Eisenbahnstr. 45 77960 Seelbach / Germany

Tel. +49 (0) 7823 51-0 info.de@julabo.com

# **JULABO Services**

Product finder, Accessory search, 1 PLUS Warranty, Catalog download, Callback service, Operating manuals, Safety data sheets, Software and more

www.julabo.com

**F500** 2/2

Technical changes without prior notification. Images may deviate from the original.